



Fury.Honda.com



SPECIFICATIONS*

ENGINE

Engine Type	1312cc liquid-cooled 52° V-twin
Bore and Stroke	89.5mm x 104.3mm
Induction	PGM-FI with automatic enricher circuit, one 38mm throttle body
Ignition	Digital with three-dimensional mapping, two spark plugs per cylinder
Compression Ratio	9.2:1
Value Train	SOHC; three valves per cylinder

DRIVE TRAIN

Transmission	Five-Speed
Final Drive	Shaft

CHASSIS / SUSPENSION / BRAKES

Front Suspension	45mm fork; 4.0 inches travel
Rear Suspension	Single shock with adjustable rebound damping and five-position spring preload adjustability; 3.7 inches travel
Front Brake	Single 336 mm disc with twin-piston caliper
Rear Brake	Single 296 mm disc with single-piston caliper
Front Tire	90/90-21
Rear Tire	200/50-18

DIMENSIONS

Rake	(Caster Angle): 38.0°
Trail	3.5 inches
Wheelbase	71.24 inches
Seat Height	26.7 inches
Curb Weight	663 pounds (Includes all standard equipment, required fluids and a full tank of fuel—ready to ride)
Fuel Capacity	3.4 gallons

OTHER

Emissions	Meets current EPA standards. California version meets current California Air Resources Board (CARB) standards and may differ slightly due to emissions equipment
Available Colors	Ultra Blue Metallic, Black, Metallic Silver, Dark Red Metallic, Matte Silver Metallic

FACTORY WARRANTY INFORMATION

One Year	Unlimited-mileage limited warranty; extended coverage available with a Honda Protection Plan.
----------	---

*All figures are preliminary and subject to change.

©2009 American Honda Motor Co., Inc. - Motorcycle Division